

Control Cabinet TK 250-500-750

For sound emitters and PA systems



The amplifier unit has an integrated thermally compensated battery charger. Simple operation with a 128x64 pixels graphic display and the logging of all activities. Each sound channel is programmable for an optional output between 0 > 375 W, with individual frequency adjustment for the optimal alarm effect in conjunction with the Delta sound emitters.

CE-labelled and complies with Directives 72/23/EEC and 89/336/EEC as well as the norms EN 60065, EN 61000-6-2 and EN 61000-6-3.

Ref. no. 255.30.314

Supply voltage	85-264V AC
Power consumption, idle	105 V/A
Power output	2 x 125W or 2 x 250W or 2 x 375W
Battery, 2 x	12V/17Ah
Thermally compensated charging	Yes
Principle of operation	Class D
Efficiency	85%
Duty cycle	25%
Graphic display	128 x 64 pixels
Buttons	4 x
Alarm tones	6 x
Additional inputs	2 x
Microphone input	Yes
Line-in	Yes
Storage of spoken messages	60 seconds
Interfaces	RS-232, RS-485, USB, CAN
Protocol	As per customer specification
Logging function	500 occurrences
Status outputs	15 x via open collector
Common alarm relay	1 change-over contact 250V AC/1A
Operating ambient temperature	-25°C ... +50°C
Protection rating	IP65
Dimensions W x H x D	500 x 500 x 210
Weight excl. batteries	20kg
Weight incl. batteries	32kg
Colour	RAL 7035, light grey
Cable glands	1 x M20 for cable diameter 8-13mm 3 x M16 for cable diameter 5-9mm

